

▼ CBD20-150



Characteristics

- Electronic power steering system.
- AC Driving system.
- Electromagnetic, regenerative braking system.
- Automatic lifting limit.
- Curve automatic deceleration devices.
- Stepless speed control system.
- Emergency reversing device.
- Emergency brake switch.
- Option: 140Ah VRLA Battery-Built-in charger. Handle upright walking function.
- Option: Fork lowered height 75mm
- Option: Lithium battery

Model			CBD20-150
Loading capacity	kg		2000
Load center	mm		600
Operating type			Walkie
Wheels type			PU
Driving wheel size	mm		φ248×75
Max.lifting height	mm		110
Overall fork width	mm		540/600/650/685
Fork length	mm		1150/1200
Fork width	mm		170
Fork thickness	mm		75
Overall length	mm		1750
Overall width	mm		720
Overall height(With handle)	mm		1385
Min.Turning radius	mm		1575
Min.Aisle width for pallets 1000×1200	mm		1940
Travel speed,laden/unladen	km/h		3.5/4.0
Lift speed,laden/unladen	mm/s		20/25
Gradeability,laden/unladen	%		6/16
Driving motor	kW		ACL5
Lift motor	kW		DCL2
Battery voltage/capacity	V/Ah		24/210
Controller			ZAPI
Battery weight	kg		192
Service weight with battery	kg		605

