



PENDULUM TYPE CONCRETE VIBRATOR



**Concrete Vibrator c/w
Drive Unit Turnable
Frame.**

**Concrete Vibrator
TCV-32, 38, 45 & 60**



Model	TCV-32	TCV-38	TCV-45	TCV-60
Vibrator Head Diameter × Length (mm)	32 × 480	38 × 500	45 × 505	60 × 505
Flexible Shaft (mm × m) Diameter × Length	Ø10 × 6.0	Ø10 × 6.0	Ø12 × 6.0	Ø10 × 6.0
Rubber Hose (mm × m) Diameter × Length	Ø28 × 6.0	Ø28 × 6.0	Ø32 × 6.0	Ø32 × 6.0
Amplitude (mm)	1.2	1.6	2.0	2.4
Vibration per Minute (v.p.m)	9000-12500	9000-12500	9000-12500	9000-12500
Overall Weight (kg)	17.0	17.5	18.0	23.5

Description

Model: EY20D

Robin EY20D petrol engine with coupling and fixed frame.

Features

- 100% ORIGINAL ROBIN EY20 ENGINE
- Durable
- For most home DIY work
- Great for both home and professional use
- Value for money
- Simple mechanism provides reliable function
- Long, lasting and durable
- Safe to use

Specifications

Type	Air-cooled, 4-cycle, upright single cylinder, side, valve, horizontal PTO shaft
Bore x Stroke mm(in.)	67x 52(2.64 x 2.05)
Piston displacement cc(cu.in.)	183(11.17)
Continuous output kW(HP)/rpm	2.2(3.0)/3000 2.6(3.5)/3600
Maximum output kW(HP)/rpm	3.7(5.0)/4000
Maximum torque N · m(kgf · m)/rpm(lbf · ft/rpm)	9.3(0.95)/2800, (6.87/2800)
Direction of rotation	Counter clockwise as viewed from PTO shaft side
Fuel	Automobile(unleaded)gasoline

Fuel	Automobile(unleaded)gasoline
Fuel Tank capacity liter(US gal.)	3.8(1.00)
Lubricant	Engine oil SAE 10W-30, 20W, 30W
Lubrication	Mechanical splashing type
Lubrication oil capacity liter(US gal.)	0.6(0.156)
Carburettor	Float type
Starter	Recoil starter
ignition system	Transistorised
Spark plug	NGK B6HS
Governor	Centrifugal flyweight type
Dry weight kg(lb)	15.2(33.52)