

ELECTRIC MOTOR DRIVE

AS0812E (Indoor Use / Outdoor Use)

- Optimization and match of hydraulic system delivers longer lasting performance
- Optimized electronic control system for better brake ability on a long downhill
- Improved steering mechanism reduces tire wear during turning
- Battery powered with zero emission and environmental-friendly

PRODUCT SPECIFICATION	AS0812E	AS0812
Platform Capacity	450kg	450Kg
Capacity On Deck Extension	113kg	113Kg
Platform Occupants (Indoor)	2	2
Work Height	10m	10m
Overall Length	2.42m	2.42m
Overall Width	1.18m	1.18m
Overall Height - Rails Down	1.73m	1.73m
Overall Height - Rails Up	2.30m	2.3m
Platform Extension	0.9m	0.9m
Drive Speed (Lowered/Elevated)	4/0.8km/h	3.5/0.8Km/h
Lift / Lower Time	35/40sec	35/40sec
Gradeability	25%	25%
Max. Slope	1.5°/3°	1.5°/3°
Machine Weight	2,715kg	2,691Kg

HYDRAULIC MOTOR DRIVE

AS0812 (Indoor Use / Outdoor Use)

- Most durable and reliable scissor stacks
- Reinforced working platform
- Advanced charger with voltage protection
- Higher driver comfort and security

