

<p>FYL-1200 (2900kg)</p>		<p>Walk speed:0-12km/h Gradeability:30-40% Drive type:hydraulic transmission Vibration type: hydraulic vibration Vibration frequency:60Hz Exciting force:2x30KN Water tank:200L Hydraulic oil tank:48L Engine type:Perkins Diesel 403D-15 Power:32.7HP Starting mode:Electric Steel drum size:φ700X1200mmX2 Net weight:2900kg Size:2495X1310X2485mm</p>	<p>1). Full hydraulic system, CVT speed; 2). Double drums hydraulic driving; 3). Hydraulic turning; 4). Double drums hydraulic vibrating or front drum hydraulic vibrating can be switched. =====</p> <p>* Hydraulic pump brand: Danfoss (USA) *Hydraulic driving motor brand: Poclain (Italy) *Hydraulic vibrating motor brand: Vivolo (Italy) *Steering gear brand: Eaton (USA)</p>
------------------------------	---	---	---

	<p>Walk speed:0-4km/h Climbing capacity:30% Drive type:Hydraulic Station Vibration Control: Automatic Clutch Static linear load:53N/cm Vibration frequency:70HZ Exciting force:20KN Water tank:20L Hydraulic oil tank:21L Engine model:water-cooled diesel CD180 Power:7.0HP Starting Mode:Hand and Electric Steel Wheel Size:φ425X600mmX2 Net weight:550kg Packing Size:1450X1100X1200mm</p>
--	---

	<p>Engine:Air Cooled Diesel CF178 Power:6.0HP Working area:500*690mm Walking:Machinery double-way Vibrating force:30KN Frequency:70HZ Grade ability:25% Starting mode:Hand /electric Weight: 300kg Packing size:780*560*1060mm</p>
---	--