

# TOKU<sup>TM</sup>

## TAMPING RAMMER

### The Objective of Compaction:

- Rockfill
- Clay Soil
- Sand & Gravel

### Application:

- Backfilling Work
- Embankment
- Road Repairing Work
- General Construction Work

### Features:

- Tamping plate is made of High Quality Steel for maximum durability.
- High performance.
- 360mm (L) × 300mm (W) plate size designed for well balance and better tamping efficiency.
- Specially designed handle with anti vibration rubber mounted to reduce operator fatigue during operation.
- Direct drive from engine, powerful, stable in usage.



**ROBIN EY-20D**



**ROBIN EH-12D**



**HONDA GX-160**

Model	<b>TK-72B</b>		
Shoe Size L × W (mm)	330 × 280		
Blow/Min (vmp)	630-700		
Fuel Tank Capacity (lt)	2.0		
Fuel Consumption (lt/hr)	1.1		
Travel Speed (m/min)	9-11		
Impact Force (kgf)	1400-1600		
Lubricating system	Oil Bath		
<b>Engine</b>	<b>Robin EY-20D</b>	<b>Robin EH-12D</b>	<b>Honda GX-160</b>
Max Output (rpm)	5.0/3600	3.8/4000	5/4000
Engine Type	Gasoline	Gasoline	Gasoline
Weight (kg)	73	73	75
M'ment (L x W x H) (mm)	760 x 430 x 940		