

SMALL 50



SMALL 50

- Has the ability to spray/pump up to 3.5 gallons of material per minute through 85FT of 1" hose.
- Able to spray fireproofing, pump grout into door jams, fill moulds at precast plants, spray stucco onto the residential home, apply grout to finish rock walls.

STEP 120

- For spraying & pumping conventional mortar and premixed plasters, fibre-reinforced and refractory mortars, grouting, fireproof materials, self-leveling screeds, for reinforcing injections at controlled pressure.
- It can also perform high volume grouting at required controlled pressure.



STEP 120

Note: SG max grain size shall be 2mm less than the stated spec above max grain size applies to Europe or the USA region only

MODEL	SMALL 50 1106040	STEP 120 1106074
BRAND	IMER	
MOTOR POWER RATED	1.5KW	SPEED 1-3.6KW SPEED 2-4.8KW
COMPRESSOR FLOWRATE	220L/MIN	310L/MIN
MAX GRAIN SIZE	6MM	8MM
MAX FLOWRATE	0.8-14L/MIN	17L/35L/MIN
PUMPING DISTANCE	Ø19MM-15M Ø25MM-25M	HORIZONTAL-60M VERTICAL-30M
HOPPER CAPACITY	69KG	280KG
VOLTAGE	230V, 1 PHASE ,6A	400V, 3 PHASE ,12A
DIMENSION	520X1120X650MM	820X2040X960MM
MAXIMUM PUMP PRESSURE	300PSI/20BAR	450PSI/31BAR