

# XG1614HD

## SCISSOR LIFT


### FEATURES

#### PRODUCTIVITY

- 2 front driving wheels
- 25% theoretical gradeability-stowed/lowered position
- Battery charge indicator and diagnostic display
- Manual platform lowering valve
- Both platform and ground control panel with emergency stop button
- Rear wheel multi-disc brakes
- Manual brake release system
- Solid non-marking tires
- Mobile pothole protection
- Tilt alarm
- Hourmeter screen
- Lift and lower alarm
- Horn
- Dual flashing beacons
- Drive alarm
- Overload alarm

### OPTIONS

- Platform working light
- Air-line to platform
- AC power to the platform
- AC motor
- Li-battery



Item	Unit	XG1614HD
Lift capacity	kg	350
Lift capacity of extended platform	kg	115
Occupant Capacity	-	2
Working Height	m	15.8
Platform Height	m	13.8
Extended platform size(Length x Width)	mm	900
Ground clearance(pil protector rising/descending)	mm	100/20
Turning radius(inner/outer wheel)	m	0/2.65
Lift motor	kW	4.5
Drive speed at low level	km/h	3
Drive speed at high level	km/h	0.8
Lift/Lower time	s	65~82/61~80
Gradeability	%	25
Title alarm(side/forward and backward)	°	1.5/3
Batteries	V/Ah	4 x 12/240(25.6/230)
Charger	V/A	24/30
Tires	-	381 x 127
Weight	kg	3700
a Length(without ladder)	mm	2840(2630)
b Width	mm	1390
c Height(platform folded)	mm	2721(2175)
d x e Platform size(Length x Width)	mm	2640 x 1120
f Wheelbase	mm	2240