

HERCULES

4KG · 6KG · 9KG · 12KG Multipurpose Dry Chemical Powder Fire Extinguisher CLASS AB



MODEL	FT01-04A-00	FT01-06A-00	FT01-09A-00	FT01-12A-00
Capacity	4KG	6KG	9KG	12KG
Extinguishing Agent	Multipurpose Dry Chemical Powder			
Propellant	Nitrogen			
Operation Method	STORED PRESSURE			
Test Standard	SS EN3, BS EN3			
Discharge Distance	> 3.5M	> 4M	> 5M	> 5M
Discharge Time	12 Sec	12 Sec	14 Sec	31 Sec
Body Diameter	138 MM	160 MM	185 MM	190 MM
Total Height	447 MM	520 MM	540 MM	590 MM
Total Weight	6.6 KG	9.4 KG	13.4 KG	16.6 KG
Operating Temperature	-20°C to 60°C			
Working Pressure	15 BAR			
Test Pressure	30 BAR			
Fire Rating	27A : 113B	34A : 183B	43A : 183B	55A : 233B
Pack Dimension(mm)	155x290x470 (2 per box)	165x175x535 (1 per box)	195x195x555 (1 per box)	200x200x610 (1 per box)
PART NO	FEL-FT-D04	FEL-FT-D06	FEL-FT-D09	FEL-FT-D12



EN3



SETSCO SG
APPROVED

Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.

2. **P**ull out safety pin.

3. **A**im.

4. **S**queeze handle.

5. **S**weep.

Accessories

(Default)



L Bracket

Bracket

Foot 4/6/9KG

Due to constant improvements, product dimensions may differ slightly.