## **ELECTRIC MOTOR DRIVE**

## **SS0507E** (Indoor Use / Outdoor Use)

- Optimization and match of hydraulic system delivers longer lasting performance
- Optimized electronic control system for better brake ability on a long downhill
- Improved steering mechanism reduces tire wear during turning
- Battery powered with zero emission and environmental-friendly

PRODUCT SPECIFICATION	SS0507E
Platform Capacity	230kg
Capacity On Deck Extension	113kg
Platform Occupants (Indoor)	2
Work Height	6.3m
Overall Length	1.53m
Overall Width	0.81m
Overall Height - Rails Down	1.9m
Overall Height - Rails Up	2.15m
Platform Extension	0.6m
Drive Speed (Lowered/Elevated)	4/0.5km/h
Lift / Lower Time	25/20sec
Gradeability	25%
Max. Slope	1.5°/3°
Machine Weight	970kg







AS0812





AS1012E AS0808E AS0812E AS1012 AS0808

AS1212E AS1212



## LINGONG GROUP JINAN HEAVY MACHINERY CO., LTD.

Factory address: Lingong Industrial Park, No. 2676, Kejia Road, Jinan Innovation Park Email: sales@lgmg.com.cn (Overseas)

Manufacturer's Representative for ASEAN

## **OMNI MACHINERY PTE LTD**

31 Gul Drive Singapore 629479 info@omni-machinery.com Http://www.omni-machinery.com