

XGA26

Parameter

| Item | Item | XGA20 |
|-----------------------------|------------|--|
| Max. Working Height | m | 26.38 |
| Max. Platform Height | m | 24.38 |
| Max. Working Range | m | 18.9 |
| Max. Load Capacity | kg | 230 |
| 1st Boom luffing Range | ° | -1 ~ +70 |
| 2nd Boom luffing Range | ° | -35 ~ +68 |
| Fly Jib Luffing Range | ° | -60 ~ +70 |
| Rotation Angle of Turntable | ° | 360° (Continuous) |
| Rotation Angle of Platform | ° | 160 |
| Max. Tail Wagging | mm | 1330 (Boom lifted) |
| Max. Travel Speed | km/h | 5 |
| Min. Turning Radius | m | 4.2m (Four turn) / 6.7m (Two turn) |
| Min. Ground Clearance | mm | 260 |
| Max. Grade Ability | % | 45 |
| Tire Specification | - | 18/625 |
| Engine Model | - | Foton Cummins QSF2.8t3TC71 |
| Rated Power of Engine | kW/(r/min) | 53/(2200) |
| Total Weight | kg | 17800 |
| Platform Size | mm | 2400 × 900 |
| a Overall Length | mm | 11280 |
| b Overall Width | mm | 2490 |
| c Overall Height | mm | 3000 |
| d Wheel Base | mm | 3000 |



Work Curve Graph

